

Strike Jamb Router DT-503 & DT-501

The Dotul strike jamb router model DT-501 is specifically used to machine an interior or exterior jamb. It can machine a flat, rabbeted or split jamb. While the Dotul strike jamb router model DT-503 is specifically used to machine interior jambs. Both Dotul strike jamb routers are typically used with the Maverick or Nomad door machines, but can also be used with other door machines.



DT-503 Features and Benefits

- **1 3/4 HP Dewalt 616 Router, motor w/tools** - More HP for hardwoods and durability.
- **Full lip strike template** - Includes one with the machine.
- **Easy change template holder** - Makes template changes fast.
- **1/2" Threaded Mandrel with 1/2" Carbide Tip Router Bit** - Easy to change the router bits, no special adjustment needed.
- **Left Hand & Right Hand stops** - Quickly machines left or right handed interior jambs.

Options:

- Complete dust collection system
- Additional phenolic or steel templates
- Overhead material arms
- Capability to machine for "T" astragals
- Other options are available, consult with your distributor (see distributor map)

DT-501 Features and Benefits

- **Dust Collection Kit (Less Vacuum Unit)** - Standard feature on every DT-501 strike jamb router. Can be hooked up to a central dust collection system or free standing vacuum.
- **Interchangeable strike templates** - Seven of the most common strike templates are included with the DT-501 strike router.
- **Overhead material arms** - Keep specials or a bundle of your common strike jambs in easy reaching distance. Standard on each machine.
- **Template Tray** - Easy accessibility to a variety of templates.
- **Deadbolt stops** - Change from standard stops to deadbolt stops in seconds. Standard on each machine.
- **1 3/4 HP Dewalt 616 Router, motor w/tools** - More HP for hardwoods and durability.
- **Full lip strike template** - Phenolic or steel templates can be used for longer life.
- **Easy change template holder** - Makes template changes fast.
- **1/2" Threaded Mandrel with 1/2" Carbide Tip Router Bit** - Easy to change the router bits, – no special adjustment needed.
- **Left Hand & Right Hand stops** - Quickly machines left or right handed interior or exterior jambs.

Options:






- Vacuum to add to the dust collection
- Additional phenolic or steel templates
- Capability to machine for "T" astragals.
- Other options are available, consult with your distributor. (see back page)

DT-501 & DT-503
SPECIFICATIONS

Door Width - N/A Door Height - N/A Door Thickness - N/A Raised Moulding - N/A Jamb Thickness - N/A Jamb Width - 2-1/2" to 10-1/2"
Jamb Length - Up to 9'-0" Hinge Spacing - N/A Hinge Size - N/A Hinge Radius - N/A Lock Backset - N/A Faceplate Routing - N/A
Double Bevel - N/A Floor Space w/dust collector - 7' W x 9' L Floor Space w/o dust collector - 3' W x 9' L Minimum Height Clearance - 6'
Approximate Shipping Weight - 500 Lbs. *400 Lbs. Electrical Requirement - 110 V -1 ph Air Requirement - 1.0 CFM @ 90 PSI
Dust Collection Requirement - 500 CFM *N/A

Dotul Distributors Map
January 2015

DÖTUL
intelligent door building machinery

-   Global Sales Group, LLC
-   Akhurst Machinery
-  Dotul

Member



Member



Member

MSLBMMA

Represented By:



Global Sales Group, LLC
P.O. Box 1835 Chico, CA 95927
Toll Free (USA & Canada): 877-474-5521
Office: 530-893-2444
Fax: 530-893-2244
info@globalsalesgroupllc.com
www.globalsalesgroupllc.com



Please visit our YouTube channel for more information on our products: **Global Sales Group LLC**



Akhurst Machinery
1669 Foster's Way
Delta, BC V3M 6S7
Tel: (604) 540-1430
Toll Free: 1-888-265-4826
Fax: (604) 540-1780
Email: van@akhurst.com