## 60HA HOTAIR EDGEBANDER

## The ideal solution for businesses using manual Edgebanding methods

Our hot air edgebander applies your preferred choice of preglued edgebanding.

Reduce the amount of panels discarded due to unsatisfactory edge banding installation. The 60HA features electronic variable speed control, digital temperature control, electromagnetic end cutters, an accutrim edge trim system and more.

The innovative design of this American-Made machine makes it easy to use and provides a very dependable edgebanding solution.

This machine provides the ideal solution for those edgebanding inefficiently.




## **Features**

- Electronic variable speed feed and digital electronic temperature control.
- Adjustable heat nozzle saving energy. ٠
- Micro adjust tape guide makes chang-• ing tape widths fast and simple.
- Electromagnetic end cutters means no • need for compressed air supply.
- Accutrim edge trim system uses industrial ٠ duty trim router motors to ensure quality finish.
- Dust collection outlet keeps trimmings off your work piece and the floor.
- Automatic conveyor for consistent feed rate. •
- Solid edge flush trimming and edge molding • capability.
- Machined billet aluminum components. ٠
- Easy to set-up, operate, and maintain. •
- Small footprint.
- American made with 3 year warranty.





Adjustable Heat Nozzle Pressure Roller .



60HA, Hot Air Edgebander	
Weight	333lbs/151kg
Dimensions (shop)	68" × 48" × 36"
Power Supply	220V, 20 amp, 1~
Tape Types	Preglued Polyester/PVC/Wood
Tape Widths	1/2"/13mm to 1.75"/45mm
Min. Panel Length	6"/152mm
Min. Panel Width	3.5"
Max Tape Thickness	1mm
Max Feed Rate	up to 15 FPM



Safety Speed Manufacturing • 13943 Lincoln St NE • Ham Lake, Minnesota 55304