

## **TA SERIES** TABLE SAWS



#### Authorized Dealer:

Global Sales Group, LLC P.O. Box 1835 \* Chico, CA 95927 Toll Free: 877-474-5521 Office: 530-893-2444 www.globalsalesgroupllc.com



# TA SERIES | TABLE SAWS

### Powerful industrial 10" - 16" cabinet table saws.

The Cantek TA Series Table Saws are for serious woodworkers and production shops that require an industrial strength and powerful table saw. The large precision-ground & polished cast-iron table and cast-iron saw unit ensure vibration free cutting with optimum cut quality. The quick setting T-square rip fence is equipped with dual inch & metric scales for precise rip cutting. The blade guard is mounted to a splitter with anti-kickback pawls for safe operation. Comes standard with both standard and dado arbors and table inserts. Driven by a powerful motor to make the cuts you need effortlessly.



T-square 50<sup>°</sup> rip fence



Blade guard with anti-kickback splitter



Blade height and tilt adjustment handwheels



Dado arbor and insert



Magnifying lens



Right tilt to 45°



Miter gauge with T-miter slot on both sides of the table



CSA / UL approved magnetic switch

### Key Advantages.

- Heavy-duty cast iron table is precision ground for accuracy & precision
- Industrial strength cast iron saw carriage and trunnion for vibration free cutting
- 50" capacity T-square rip fence assembly locks on front rail for a precise parallel reference to the saw blade
- Right tilt blade to 45°
- Dual Inch/Metric scale guide rail on rip fence with magnifying glass for easy visibility
- Miter gauge with two miter slots in the table
- Comes with dado arbor & dado table insert
- New Feature for TA16: 16" blade can be lowered completely under the table
- Rugged machine frame construction provides maximum stability and reduced vibration
- Saw guard with built in splitter and safety anti-kickback unit
- Dado arbor and insert included along with appropriate cast iron table inserts
- Handwheel adjustment for blade height and tilting adjustments which can be locked in place
- CSA / UL approved magnetic switch

#### Specifications.

|                            | TA10    | TA10-5  | TA12    | TA14    | TA1214  | TA16B   |  |
|----------------------------|---------|---------|---------|---------|---------|---------|--|
| Saw Blade Diameter         | 10"     | 10"     | 12"     | 14"     | 14"     | 16"     |  |
| Max. depth of cut at 90°   | 3"      | 3"      | 4"      | 5"      | 5"      | 5 1⁄2″  |  |
| Max. depth of cut at 45°   | 2"      | 2"      | 2 ¾″    | 3 1⁄2″  | 3 1⁄2″  | 3 7/8"  |  |
| Arbor diameter             | 5/8"    | 5/8"    | 1"      | 1"      | 1"      | 1"      |  |
| Dado arbor diameter        | 5/8″    | 5/8″    | 5/8″    | 1″      | 1″      | 1″      |  |
| Arbor speed (RPM)          | 4200    | 4200    | 4000    | 3750    | 3750    | 3750    |  |
| Table size                 | 36"x27" | 36"x27" | 48"x30" | 48"x38" | 48"x38" | 48"x38" |  |
| Table height               | 34 1/4" | 34 1/4" | 34 ¼"   | 34 ¼″   | 34 ¼"   | 34 ¼"   |  |
| Max. rip to right of blade | 50"     | 50"     | 50"     | 50"     | 50"     | 50"     |  |
| Motor                      | 3HP     | 5HP     | 5HP     | 7.5 HP  | 10 HP   | 10 HP   |  |
| Net weight                 | 407 lbs | 407 lbs | 572 lbs | 847 lbs | 847 lbs | 869 lbs |  |