

The logo for CANTEK, featuring the word "CANTEK" in a stylized, italicized font with a red outline, set against a white background within a red-bordered box.

MX350M

AUTOMATIC EDGE BANDER



Authorized Dealer:

Global Sales Group, LLC

Toll Free: 877-474-5521

Office: 530-893-2444

www.globalsalesgroupllc.com



MX350M | AUTOMATIC EDGE BANDER

Compact edgebander with pre-milling for best-in-class results.

The Cantek MX350M Automatic Edgebander is an entry level edgebander with pre-milling that is the perfect blend of quality and affordability. With fine attention to detail and quality componentry, the MX350M can output high quality edges on cabinet parts and more. The pre-milling diamond cutterheads machine the panel just prior to applying the glue to ensure optimum edge quality prior to applying the edge tape. Additionally, the machine is equipped with end trimming, flush trimming, PVC scraping, and buffing. User friendly controls and adjustments allow for efficient changeovers of edge tape thicknesses between 0.4mm & 3mm.



Operating panel with LED Keypad



Edge feeding coil



Heavy duty chain feeding



Teflon-coated glue pot



Pressure roller



Guillotine shear



Pre-milling Unit



End trimming unit



Flush and radius trimming unit



Scraping unit



Buffing unit

Key Advantages.

- Compact design makes it the ideal edgebanding solution for small workshops
- Pre-milling the panel ensures optimum edge quality prior to edgebanding
- Precise adjustments for optimum edge quality
- Chain feed system ensures consistent feeding of material for consistent results
- Available in 230V 1 or 3 phase
- PLC control system with LED display and keypad
- Workpiece is fed by chain
- Edge coil support plate: Ø 800 mm (31.5"), for PVC/ABS
- Automatic edge feeding with a thickness capacity of 0.4-3 mm; strip material up to 4mm can be hand-fed
- Coiled edge bands up to 3 mm in thickness in Hard-PVC/ABS are cut with guillotine shears.
- 2 kg (2.64 lb) Teflon-coated hot-melt glue pot
- Spring loaded pressure unit with (2) pressure rollers (1 chrome & 1 rubber)
- Heavy duty pressure beam with extendable work-piece support
- Heated infeed fence for pre-heating the panel for optimum glue penetration
- Mechanical digital readouts for convenient and quick adjustment to the working units & thickness

Working Units.

PRE-MILLING | Pre-milling unit with (2) counter rotating diamond cutterheads for precise edge quality

END TRIM | 8800 RPM dual saw blade (80mm / 3.15") end trimming unit

TOP & BOTTOM TRIM | 10500 RPM top & bottom trimmers with insert knife cutters for radius trimming & bevel trimming

RADIUS SCRAPING | Radius scraper with 2mm radius knives can be easily excluded when not required

BUFFING | 2800 RPM top & bottom buffing units to polish the machined edge

Specifications.

Feeding speed	23 FPM
Panel thickness	0.472~1.77"
Edge thickness	0.0158"~0.118"
Minimum panel size	3.54" x 8 3/4"
Working table height	33.7"
Dust collection outlet dia.	4"
Pre-milling spindle speed	9000 RPM
Max. machine dimensions (LxWXH)	126" x 47 1/4" x 47 1/4"
Machine weight	1162 lbs