



Authorized Dealer:
Global Sales Group, LLC
P.O. Box 1835 * Chico, CA 95927
Toll Free: 877-474-5521
Office: 530-893-2444
www.globalsalesgroupllc.com



TS-600RR
TS-900RR
TS-1200RR

2' Two Rolls Coater Machine
3' Two Rolls Coater Machine
4' Two Rolls Coater Machine

Optional:

- TS-600DR 2' DUST REMOVE CONVEYOR
- TS-600C 2' W x 8' L POWER CONVEYOR
- TS-600HC 2' HEAT CONVEYOR
- TS-102W 1' U.V. CURING M/C

Features:

- Designed and built for the best coating performance.
- The roll coater is well-suited for coating materials such as: knockdown furniture, wood toys, wood-figure assembling parts, plastic products, rubbers, leathers, foaming shoes, etc.
- They are capable of surface coating, color dying and printing.
- With the roll coating principle, you simply place the workpieces on the conveyor belt, they will automatically move through the rolls; a coating operation is quickly accomplished.
- Uniform coating thickness. You get superior finishing effect without the need of a skilled technician.
- Rollers are covered with high quality rubber ensuring absolute anti-solvent.



- Top quality resin conveyor belt ensures stretch and long service life. Fast cleaning and easy belt tracking with the hand wheel.
- Working thickness and coating thickness adjustment is easily made with hand wheel.
- Transmission motor infinitely variable feed rate 65' ~ 204' per minute suited to coat various lengths of workpieces.
- Eliminates air pollution problems; clean working environment with safety.
- A comparison for coating same area of workpiece, the roll coaters can save at east 20% labor cost and 30% coating material than conventional coating method.
- Free from moisture affecting (foggy) while operation under bad weather, coating still can be performed.
- Increase the coating efficiency get the best surface finish the wide versatile LOBO roll coaters are the ideal machines for you.

SPECIFICATIONS	TS-600RR	TS-900RR	TS- 1200RR
Max. Coating Width	24"	37"	50"
Max. Coating Thickness	1/12" ~ 1-1/4"	1/12" ~ 1-1/4"	1/12" ~ 1-1/4"
Mm. Coating Length	6"	6"	6"
Feed Speed (infinitely variable)	68' ~ 204'	68' ~ 204'	68' ~ 204'
Coating Rolls	2 PCs	2 PCs	4 PCs
Conveyor Belt Motor	1 HP	2 HP	2 HP
Pump Motor	1 HP	1 HP	2 HP
Machine Dimension (L X W X H)	4.5' x 4' x 4'	5' x 5' x 4.5'	5.5' x 6' x 4.5'
N.W.	1100 LBS	1430 LBS	1760 LBS
G.W.	340 LBS	1510 LBS	2100 LBS

(Training and installation, tooling & rigging are optional)
(Customer is responsible for local regulations and connecting utilities)