



Authorized Dealer:
Global Sales Group, LLC
P.O. Box 1835 * Chico, CA 95927
Toll Free: 877-474-5521
Office: 530-893-2444
www.globalsalesgroupllc.com



ST-483FD 4-Speed 4-Roller Feeder

Features:

- With the powerful feeding strength, one can freely & simply assemble, dismantle & adjust it. It may be installed onto the circular saw, shaper, sander, router, planer serving as one's invisible third hand at work.
- There are four (4) feed rollers on this feeder. Each roller has a suspender to hold simultaneously the workpiece at different degrees of thickness. It is also used to help the feed pressure.
- In case you need a large space between the rollers, you can take off the middle roller so the remaining rollers may be used for curve driving.
- For spindle molder, the feeder may be adjusted to the leveling direction for side feed to meet the requirement of various processing condition.
- There are two (2) sets of matching & interchangeable gears of variable sizes to create for stages of feeding speed.
- Forward & reverse feeding switch.
- Universal support stand with cast iron base, main bracket, thick refaced column and aluminum hand wheels for vertical and horizontal positioning.

Options:

- ST-30FRL ROLLER FOR ST-30
- ST-30BT BASE FOR ST-30

SPECIFICATIONS	ST-483 FD	ST-3 VFD	ST-TANK
Feeding Speed (FPM)	6 ~ 102 (8S)	10 ~ 79 VAR	6 ~ 102 (8S)
Roller Size	4-3/4" x 2 3/8"	4-3/4" D x 2-3/8" W	10" BELT
Motor	1 HP, 1 PH, 230 V	1 HP, 3 PH, 230 V	1 HP, 3 PH, 230 V
Roller Suspension	1"	1"	1"
N.W.	160 LBS	143 LBS	134 LBS
G.W.	220 LBS	154 LBS	147 LBS

(Training and installation, tooling & rigging are optional)
(Customer is responsible for local regulations and connecting utilities)