



Authorized Dealer:
Global Sales Group, LLC
P.O. Box 1835 * Chico, CA 95927
Toll Free: 877-474-5521
Office: 530-893-2444
www.globalsalesgroupllc.com



2 HEADS

WS-NA900	36" 1 Head Planer, 1 Head Sander
WS-NDA900	36" 1 Head Planer, 2 Head Sander
WS-NA1300	52" 1 Head Planer, 1 Head Sander
WS-NDA1300	52" 1 Head Planer, 2 Head Sander

Option:

- CT-SCH14T 14MM x 14MM SPIRAL CUTTERHEAD BLADES

Features:

- This machine is especially designed for take off heavy material such as glue panel, bend board, and rough lumber.
- The first station is a knife planer head, followed with a combination drum & platen head at second station.
- Head configuration can be made to meet customer's requirement.
- The spiral planer cutterhead is fitted with 14 x 14 mm, four edge throw away tungsten carbide knife insert, providing superior chip removal rate, minimum noise, and extremely smooth cutting effect.
- Changing knife inserts are conveniently made without removing the cutterhead. The spiral cutterhead is precision machined from special aluminum alloy steel by CNC machine center, tempered and precision ground.

- Anti-kickback fingers mounted at the infeed of the machine, this anti-kickback finger gives a safety guard for the operator.
- Insufficient pressure protection in case insufficient working air pressure occurs, the machine brakes automatically for safety guard.
- Irreversible running of pressure roller, runs a single direction only, which gives an additional safety guard for panel kickback.
- Automatic elevation of conveyor table (micro-computer controlled with digital readout), it accurately displays the position of the conveyor table and automatic moves to the setting thickness for planing, sanding.
- Panel cleaning brush roller; built at outfeed end of the machine, this cleaning brush roller cleans the powder on the sanded panel.
- Hold down plate is hard chrome treated for maximum wear resistance.

SPECIFICATIONS	WS-NA900	WS-NDA900	WS-NA1300	WS-NDA1300
Working Width	36"	36"	52"	52"
Working Thickness	5"	5"	5"	5"
Min. Working Length	12½"	12½"	14½"	14½"
Main Motor (Standard)	25, 20 HP	25, 20, 20 HP	30, 25 HP	30, 30, 25 HP
Feeding Motor	3 HP	3 HP	5 HP	7½ HP
Table Hoist Motor	½ HP	½ HP	1 HP	1 HP
Feeding Speed (Variable)	10 ~ 53 FPM	10 ~ 53 FPM	10 ~ 53 FPM	10 ~ 53 FPM
Sanding Belt Size	37" x 75"	37" x 75"	52" x 84"	52" x 84"
Machine Size (L x W x H)	83" x 81" x 81"	98" x 84" x 81"	107" x 87" x 80"	107" x 103" x 80"
N.W.	6000 LBS	8200 LBS	7700 LBS	10100 LBS
G.W.	7100 LBS	9100 LBS	8800 LBS	11200 LBS

(Training and installation, tooling & rigging are optional)
 (Customer is responsible for local regulations and connecting utilities)



DIGITAL THICKNESS SET UP



3 Heads