



Authorized Dealer:
Global Sales Group, LLC
P.O. Box 1835 * Chico, CA 95927
Toll Free: 877-474-5521
Office: 530-893-2444
www.globalsalesgroupllc.com



2 HEADS

WS-NA600	25" 1 Head Planer, 1 Head Sander
WS-NDA600	25" 1 Head Planer, 2 Head Sander
WS-NA1100	43" 1 Head Planer, 1 Head Sander
WS-NDA1100	43" 1 Head Planer, 2 Head Sander

Optional:

- CT-SCH14T 14MM x 14MM SPIRAL CUTTERHEAD BLADES

Features:

- This machine is especially designed for tail off heavy material such as glue panel, bend board, and rough lumber.
- The first station is a knife planer head, followed with a combination drum & platen head at second station.
- Head configuration can be made to meet customer's requirement.
- The spiral planer cutterhead is fitted with 14 x 14 mm, four edge throw away tungsten carbide knife insert providing superior chip removal rate, minimum noise and extremely smooth cutting effect.
- Changing knife inserts are conveniently made without removing the cutterhead. The spiral cutterhead is precision machined from special aluminum alloy steel by CNC machine center, tempered and precision ground.

- Anti-kickback fingers mounted at the infeed of the machine; this anti-kickback finger gives a safety guard for the operator.
- Insufficient pressure protection in case insufficient working air pressure occurs, the machine brakes automatically for safety guard.
- Irreversible running of pressure roller runs a single direction only, which gives an additional safety guard for panel kickback.
- Automatic elevation of conveyor table (micro-computer controlled with digital readout); it accurately displays the position of the conveyor table and automatically moves to the setting thickness for planing, sanding.
- Panel cleaning brush roller built at outfeed end of the machine; this cleaning brush roller cleans the powder on the sanded panel.
- Hold-down plate is hard chrome treated for maximum wear resistance.

SPECIFICATIONS	WS-NA600	WS-NDA600	WS-NA1100	WS-NDA1100
Working Width	25"	25"	43"	43"
Working Thickness	4"	4"	4"	4"
Min. Working Length	18½"	18½"	18½"	18½"
Main Motor	15, 15 HP	15, 15, 10 HP	25, 20 HP	25, 25, 20 HP
Feeding Motor	3 HP	3 HP	5 HP	7½ HP
Table Hoist Motor	½ HP	½ HP	1 HP	1 HP
Feeding Speed Variable)	10 ~ 53 FPM	10 ~ 53 FPM	10 ~ 53 FPM	10 ~ 53 FPM
Sanding Belt Size	25" x 75"	25" x 75"	43" x 98 "	43" x 98"
Machine Size (L x W x H)	71" x 50 " x 81"	88" x 50 " x 81"	107" x 81" x 90"	121" x 81" x 90"
N.W.	5200 LBS	6400 LBS	7200 LBS	11100 LBS
G.W.	5900 LBS	7300 LBS	8100 LBS	12200 LBS

(Training and installation, tooling & rigging are optional)
 (Customer is responsible for local regulations and connecting utilities)



DIGITAL THICKNESS SET UP



3 Heads