



R18

HEAVY DUTY STRAIGHT LINE RIPSAW
"Cuts from below"



FEATURES

- Extra heavy main frame throughout with large support table
- 6" minimum length with this type of saw the blade is cutting downwards ie. Forcing the Blade onto the chain hence max. stability and safety are realized.
- Better chip clearance for shavings on deep cutting
- Glue joint range – 12" to 10 Ft.
- Depth of cut 4.7" (120mm) max.
- Split chain – double track with HRC60 Rockwell Hardened Guideways
- 26" (660mm) saw to column
- 8 press rolls hold material firmly on the track
- 15 HP direct drive
- 2 HP feed motor
- Feed speed 33 to 180 FPM variable
- Automatic chain and track oiler
- 41" length of chain above table
- Saw arbor height adjustable
- Max. 18" Blade Ø x 2" Bore Ø saw Arbor with 14mm pin at 65mm centers
- Saw arbor brake Included
- Anti-kickback fingers top and bottom
- Dust collection outlets:
 - Top 5.75" 700 CFM
 - Bottom 5" 550 CFM
- Table dimensions – 82" x 40" x 33.5" high
- Net weight - 4400 lbs
- Stock machine electrics 460/3/60 to UL/CSA Standards (Other voltages available on request)

OPTIONS AVAILABLE

- 20HP Main Drive motor - Direct drive
- 3HP Feed Motor
- Outside Side Safety Guard, rear pressure device
- Bottom row of anti-kickback fingers pneumatically activated
- Pneumatic Locking Floating Fence System max range 24" - shift speed up to 24"/sec.
- 20 Mw Laser Unit In Line, 110 volt c/w universal mounting bracket



Authorized Dealer:
Global Sales Group, LLC
P.O. Box 1835 * Chico, CA 95927
Toll Free: 877-474-5521
Office: 530-893-2444
www.globalsalesgroupllc.com