







**Authorized Dealer:**  
Global Sales Group, LLC  
P.O. Box 1835 \* Chico, CA 95927  
Toll Free: 877-474-5521  
Office: 530-893-2444  
www.globalsalesgroupllc.com



### Cutting Applications:



**BS-700PF**  
**BS-800PF**  
**BS-900PF**

**28" Band Rip Saw with Feeder**  
**32" Band Rip Saw with Feeder**  
**36" Band Rip Saw with Feeder**

### Features:

- Feed roller movement is actuated by air cylinder for powerful feeding force.
- The side guide is micro metrically adjustable providing convenient adjustment for narrow blades.
- The saw wheels are laminated with rubber for accurate blade tracking and slippage prevention.
- The table is made of cast iron and the surface is precision ground.
- The table can tilt to a maximum of 45-degrees front downward for bevel cuts.
- Blade tension can be conveniently adjusted by means of a band wheel. A tension scale allows the operator to correctly adjust the tension for different blade widths.
- The cast iron top and bottom saw wheels are precision machined and dynamically balanced for smooth running.
- The see through guard provides operator safety and protection.
- The foot brake permits the quick shut down of machine operations.
- The heavy gauge steel frame ensures stable and vibration-free cutting.

- 4" diameter exhaust chute supplied as standard.
- A foot pedal allows feeder fast swing away.
- An infinitely variable feeder speed for cutting various types of wood materials, both soft and hard.
- A centralized control panel located at the normal operating position for convenient machine control.
- An amp meter indicates the percentage of motor load.
- The heavy gauge steel frame ensures maximum stability.



- Frequency inverter. It provides various cutting speed to suit all types of wood.

SPECIFICATIONS	BS-700PF	BS-800PF	BS-900PF
Saw Wheel Diameter	27-1/2"	31-1/2"	35-1/2"
Max. Distance :Fence to Feed Wheel	7-1/4"	7-3/4"	8-5/8"
Max. Distance :Blade to Feed Wheel	7-1/2"	7-1/2"	7-1/2"
Max. Cutting Height	7-3/4"	10"	11-7/8"
Length of Blade	190"	209"	227"
Max Blade Width	4"	4"	4"
Table Height from Floor	32-7/8"	36-3/4"	38-3/8"
Blade Linear Speed	4944 FPM	4944 FPM	7500 FPM
Feed Feeder Speed (Variable)	26 ~ 105 FPM	26 ~ 105 FPM	26 ~ 105 FPM
Saw Wheel Drive Motor	10 HP	15 HP	20 HP
Feed Drive Motor	1/2 HP	1/2 HP	1/2 HP
Net Weight	2460 LBS	2960 LBS	3750 LBS
Machine Size (L x W x H)	89"x43"x88"	94"x45"x98"	102"x51"x100"

(Training and installation, tooling & rigging are optional)  
 (Customer is responsible for local regulations and connecting utilities)



- The heavy duty saw wheel is dynamically balanced for smooth running.
- Saw wheels run on precision bearing.



- Blade tension can be accurately read from the rule gauge.



- Automatic lubricator provides lubrication and cooling for the sawblade. It also reduces considerable noise level.