



Authorized Dealer:
Global Sales Group, LLC
P.O. Box 1835 * Chico, CA 95927
Toll Free: 877-474-5521
Office: 530-893-2444
www.globalsalesgroupllc.com



DIGITAL THICKNESS SET UP

WS-DA950 37" x 75" Wide Belt Sander Machine

Features:

- With the triple head wide belt sander, you can accurately and heavy sand your stock with the first steel & second rubber drum head and with the third combination head, you can give an unlimited fine finish.
- Rugged heavy-duty sheet metal construction designed for durability usage.
- Powerful industrial motors drive sanding and auto infeed smoothly.
- Infeed and outfeed are spring-loaded hold down rollers to ensure positive feeding without sanding mark.
- Combination platen & drum sanding head for best sanding choice such as:
 - With the platen up, the sander functions as a drum only machine, for sanding with a 40 ~ 100 grit belt.
 - With the platen and drum same level, intermediate and final finishing is possible, using a grit of 120 ~ 180.
 - With the platen down (below drum), used for the fine finishing or lacquer sealer sanding, with 180 ~ 600 grit.
- Sanding platen with a quick release and lock down design for easy removal or loading of graphite platen.
- Computerized thickness adjustments control with accurate digital readout, just key in the size desired and automatic table movement for sanding thickness within 0.005" accuracy.
- Large size diameter contact drum is dynamically balanced rubber covered spiral grooves, designed to provide considerable advantages for the effective removal of material.
- Special rubber feed belt for safe non-slipping, transporting the workpieces.
- The abrasive belts are tracked by oscillating cylinders linked to the upper roller. The edge of the belt is detected by electric eye sensor, which in turn controls the air supply to the position via solenoid valve. Also, one limit switch is located on each end top roller of the sandpaper for quick stop in case in the event of belt breakage.
- Main table designed with the convenient leveling adjustment which ensures greater stability with excellent tolerance providing variable from 0" ~ 5" range sanding thickness.
- Four (4) heavy-duty jack screws powers conveyor table elevation.

SPECIFICATIONS	WS-DA950
Working Width	37"
Working Thickness	1/8" to 6"
Minimum Working Length	12"
Sandpaper Size (W x L)	37" x 75"
Sanding Drum Size	~
Drum Sander Motor	20 HP
Combination Sanding Drum Size	7"
Platen Width	3"
Combination Sander Motor	15HP
Clean Brush Diameter	5"
Clean Brush Motor	1/2 HP
Feed Motor	2 HP
Feed Speed	15 ~ 70 FPM
Lift Motor	1/2 HP
Net Weight	5300 LBS
Machine Size	70" L x 61" W x 79" H

(Training and installation, tooling & rigging are optional)
(Customer is responsible for local regulations and connecting utilities)

