

// SERIES 35 POWERED TURNTABLE

Series 35 Powered Turntable – Durable & Programmable Turntables for Work Positioning, Systems Interface, and Productivity Improvement

S35 Powered Turntables provide workers the ability to easily rotate heavy loads. Common applications include pallet build-up and teardown, assembly, and conveyor systems. The heavy-duty design of these chain-driven industrial turntables is specially engineered to withstand the demands and abuses of an industrial environment, and is controlled automatically.

The Series 35 family of powered turntables can turn product weighing up to 6,000 lbs, and has a lowered height of 10 inches. And, when used with an Autoquip scissors lift table, these turntables further enhance both ergonomics and productivity by reducing reaching, ending, walking, and twisting associated with palletizing and other repetitive operations. The Series 35 family of turntables has been manufactured in America's heartland since 1982 and is designed to the highest standards of safety and reliability. They're the most durable, versatile, and popular lineup of lifts sold today - while still being competitively priced. And although they're available in standard options, Series 35 turntables are often customized using features engineered to fit your specific application.



Features and Benefits

- Chrome plated center kingpin prevents corrosion of the pin and reduces wear on the sprocket center bearing.
- High impact, spiral wound bearing at the main pivot point provides maintenance-free, rugged resistance to abrasion, impact, and uneven loads.
- 1/2-inch-thick steel platform minimizes deck deflection and maximizes load stability.
- High capacity needle bearing rollers reduce turning friction and minimize motor torque requirements, extending motor life.
- Adjustable torque limiter prevents damage to the motor and gearbox by "slipping" whenever over-load or jammed-load conditions occur.
- Autoquip offers an industry-best 2 year warranty on all parts as a promise that you've purchased the industry's most reliable turntable.
- Maintenance-free bearings at pivot points require no lubrication.
-
- Standard controls are prewired and drive unit is already onboard. Installation only requires the turntable to be lagged to the ground and connected to electricity.
- Chain tension is easily adjustable to minimize wear and reduce noise.
- Lag-down holes are provided in the base to allow easier relocation.
- Both single-direction and bi-directional controls are available.
- Drive motors are rated for variable frequency drive control signals
- Turntable retention system prevents the platform from tipping during any type of edge or off-center loading.
- Removable chain guards protect personnel from inadvertent contact with the powered chain.
- Minimum 3:1 structural factor of safety makes these lifts the most structurally sound lift in the industry.
- Compliance with recognized standards:
 - NFPA 70 - National Electric Code
 - ASTM - A36 - Structural Steel Standard
 - ANSI Z535 - Safety Labeling Requirements
 - AWS D.1 - Welding Standards
 - Applicable portions of OSHA 29CFR1910 - General workplace safety



Global Sales Group, LLC
P.O. Box 1835
Chico, CA 95927
Offc: 530-893-2444
Fax: 530-893-2244
www.globalsalesgrouppllc.com

Authorized Dealer for Autoquip

// SERIES 35 POWERED TURNTABLE



Models	Capacity (lbs#)	Lowered Height (inches)	Base Frame Width (inches)	Base Frame Length (inches)	Minimum Platform Width (inches)	Minimum Platform Length (inches)	Maximum Platform Width (inches)	Maximum Platform Length (inches)	Motor Size (hp)	Shipping Weight Approx# (lbs#)	Rotating Speed (rpm)
SRP-3625	2500	10	24	24	36	36	36	36	0.25	385	3.5
SRP-4225	2500	10	24	24	42	42	42	42	0.25	450	3.5
SRP-4248-25	2500	10	24	24	42	48	42	48	0.25	485	3.5
SRP-4825	2500	10	24	24	48	48	48	48	0.25	525	3.5
SRP-3640	4000	10	24	24	36	36	36	36	0.25	385	3.5
SRP-4240	4000	10	24	24	42	42	42	42	0.25	450	3.5
SRP-4248-40	4000	10	24	24	42	48	42	48	0.25	485	3.5
SRP-4840	4000	10	24	24	48	48	48	48	0.25	525	3.5
SRP-3660	6000	10	24	24	36	36	36	36	0.25	385	3.5
SRP-4260	6000	10	24	24	42	42	42	42	0.25	450	3.5
SRP-4248-60	6000	10	24	24	42	48	42	48	0.25	485	3.5
SRP-4860	6000	10	24	24	48	48	48	48	0.25	525	3.5



GLOBAL SALES GROUP, LLC

Global Sales Group, LLC
P.O. Box 1835
Chico, CA 95927
Offc: 530-893-2444
Fax: 530-893-2244

www.globalsalesgroupllc.com

Authorized Dealer for Autoquip