

Series 35 Scissor Lift Tables Have The Power and Functionality To Do It All!

Autoquip Series 35 Scissor Lift Tables are ready to help you reach new levels of performance and productivity. Each Series 35 model is designed and built to provide long-service life, durability, and outstanding lifting power.

We offer a large selection of models suited to fit most applications such as pallet handling, parts assembly, and ergonomic work positioning. Special applications where one of our standard models is not suitable, the Series 35 product line is easily modified to deliver a lift table right for you.

Series 35 models range in travel from 24" to 60" with lifting capacities up to 15,000 lbs. We offer many options and accessories to expand the versatility of your lift table - controls, portability set, accordion skirting, turntables, and more.

Our Series 35 Scissor Lift Tables offer an unsurpassed value providing years of dependable service.



Features and Benefits

- More models and standard options than any other competitive lift table allows for easy customization to meet your specific needs.
- Standard controls are prewired and internal power unit is onboard. Installation simply includes lagging the lift to the ground and connecting electricity.
- Exceptionally low lowered height allows on and off load flexibility.
- Single-piece, steel reinforced legs and a 1/4- to 3/8-inch-thick steel platform make for extremely solid construction and easy adaptability.
- Joints, the most critical wear points in the lift, feature chrome-plated, 100,000 psi, ultimate-strength pins for premium load strength and long life.
- Solid steel leg and added stiffeners provide optimal overall stability and straight, repeatable tracking of the rollers as the lift raises and lowers.
- Minimum 1/4-inch-thick steel-reinforced platform minimizes deck deflection, maximizes load stability, and greatly extends the life of the platform deck.
- Hydraulic velocity fuses completely stop lifts in the unlikely event of uncontrolled descent due to sudden hose rupture.
- Minimum 3:1 structural factor of safety makes these lifts the most structurally sound lift in the industry.
- Compliance with recognized standards:
 - ANSI MH29.1 - Safety Requirements for Industrial Scissors Lifts
 - NFPA 70 - National Electric Code
 - ASTM - A36 - Structural Steel Standard
 - ANSI Z535 - Safety Labeling Requirements
 - AWS D.1 - Welding Standards
 - Applicable portions of OSHA 29CFR1910 - General workplace safety
- On-board maintenance devices enable maintenance crews to safely and effectively block open the scissors during inspection and routine maintenance.
- Sturdy, semi-transparent polyurethane oil reservoir provides an easily visible method of checking fluid levels and eliminates oil contamination due to rust.
- Double wire braided Parker hydraulic hoses resist wear, abrasion, and leaks.
- Easy replacement of high-strength steel rollers minimizes downtime.
- Autoquip offers an industry-best 2 year warranty on all parts as a promise that you've purchased the industry's most reliable lift.



GLOBAL SALES GROUP, LLC

Authorized Dealer for Autoquip

Global Sales Group, LLC

P.O. Box 1835

Chico, CA 95927

Offc: 530-893-2444

Fax: 530-893-2244

www.globalsalesgroupllc.com

// SERIES 35



Models	Travel (inches)	Capacity (lbs#)	Lowered Height (inches)	Raised Height (inches)	Max# End Load @ Std# Platform (lbs#)	Max# Side Load @ Std# Platform (lbs#)	Base Frame Width (inches)	Base Frame Length (inches)	Minimum Platform Width (inches)	Minimum Platform Length (inches)	Maximum Platform Width (inches)	Maximum Platform Length (inches)	Motor Size (hp)	Number of Cylinders	Shipping Weight Approx# (lbs#)	Standard Hydraulic Power Unit	Raising Time Loaded (seconds)	Lowering Time Loaded (seconds)
24S25	24	2500	6.5	30.5	2500	2500	24	36	24	36	48	60	1.5	1	500	INTERNAL	8	4
24S40	24	4000	6.5	30.5	4000	4000	24	36	24	36	48	60	1.5	1	510	INTERNAL	11	5.5
24S60	24	6000	6.5	30.5	4500	4500	24	36	24	36	48	60	1.5	2	530	INTERNAL	16	8
24S80	24	8000	7	31	4500	4500	24	36	24	36	48	60	1.5	2	650	INTERNAL	22	11
36S15	36	1500	6.5	42.5	1000	750	24	48	24	48	48	72	0.5	1	580	INTERNAL	28	14
36S25	36	2500	6.5	42.5	2500	2500	24	48	24	48	48	72	1.5	1	610	INTERNAL	12	6
36S40	36	4000	6.5	42.5	3500	3500	24	48	24	48	48	72	1.5	1	620	INTERNAL	17	8.5
36S60	36	6000	6.5	42.5	3500	3500	24	48	24	48	48	72	1.5	2	650	INTERNAL	25	12.5
36S80	36	8000	7	43	3500	3500	24	48	24	48	48	72	1.5	2	750	INTERNAL	34	17
48S25	48	2500	7	55	2500	2500	24	64	24	64	48	96	1.5	1	820	INTERNAL	16	8
48S40	48	4000	7	55	3500	3500	24	64	24	64	48	96	1.5	1	830	INTERNAL	22	11
48S60	48	6000	7	55	3500	3500	24	64	24	64	48	96	1.5	2	860	INTERNAL	33	16.5
48S80	48	8000	7.5	55.5	3500	3500	24	64	24	64	48	96	1.5	2	960	INTERNAL	44	22
60S120	58	12000	12.5	70.5	12000	10000	32	90	32	90	60	120	5HP	2	4600	INTERNAL	60	60
60S150	58	15000	12.5	70.5	14000	12000	32	90	32	90	60	120	5HP	2	4700	INTERNAL	60	60
60S25	60	2500	8	68	2500	2500	32	87	32	87	60	120	1.5	1	1750	INTERNAL	22	11
60S40	60	4000	8	68	4000	4000	32	87	32	87	60	120	1.5	2	1800	INTERNAL	44	22
60S60	60	6000	8	68	4500	4500	32	87	32	87	60	120	1.5	2	1850	INTERNAL	44	22
60S80	60	8000	12	72	8000	8000	32	90	32	90	60	120	5HP	2	4400	INTERNAL	36	36
60S100	60	10000	12	72	10000	9000	32	90	32	90	60	120	5HP	2	4500	INTERNAL	36	36



Global Sales Group, LLC
P.O. Box 1835
Chico, CA 95927
Offc: 530-893-2444
Fax: 530-893-2244

www.globalsalesgroupllc.com

Authorized Dealer for Autoquip