

## Series 35 Extra Wide Scissor Lift Tables – Greater Edge Load and Stability for Wider Loads!

The wide stance of the Series 35 Extra Wide scissor lift tables add stability and support when handling wide, bulky loads. With maximum single-scissors platform widths available up to 72 inches, this family of lifts provides the safest and most cost-effective solution for handling wider loads. Travel ranges from 24 to 60 inches and a capacity range from 2,500 to 15,000 lbs. Common applications include pallet build up and tear down, and parts assembly and disassembly. Utilizing the lifts for work positioning and conveyor systems also allow for improved ergonomics, worker productivity, and factory throughput. The Series 35 family of scissor lift tables has been manufactured in America's heartland since 1982 and is designed to the highest standards of safety and reliability. They're the most durable, versatile, and popular lineup of lifts sold today -while still being competitively priced. And although they're available in standard options, Series 35 scissor lift tables are most often customized because of their versatility and vast number of models and options.



### Features and Benefits

- Lubricated-for-life composite bearings on all pivot points
- Maintenance free bearings, no greasing required
- Solid one-piece steel legs with stiffener bars
- Minimal platform deflection
- Turned, ground, polished and hard-chromed axle pins
- Extended bearing life
- Direct thrust cylinders
- Provides the lowest collapsed height
- Chrome plated cylinder rods
- Corrosion resistance adds to life of cylinder
- Double wire braided hydraulic hoses
- Extended hose life for added safety
- Velocity fuses on cylinders
- Controlled descent in case of severed hose
- Two year warranty
- Built to last with the best warranty in the industry
- Safety labels comply with ANSI Z535
- Maintenance (safety) devices
- Easy servicing of hydraulic components
- Polyethylene fluid reservoir
- Easy inspection for fluid level, condensation and pollutants
- Factory tested to 110% of capacity
- Exacting standards means it works the first time, every time
- Internally mounted and pre-wired power unit with UL listed components
- Ready to operate with zero plumbing and minimal wiring
- Built and designed in accordance with ANSI MH29.1
- Designed to meet or exceed all industry standards
- Adds to employee's safety as the lift meets all industry standards for labeling



# // SERIES 35 EXTRA WIDE



Models	Travel (inches)	Capacity (lbs#)	Lowered Height (inches)	Raised Height (inches)	Max# End Load @ Std# Platform (lbs#)	Max# Side Load @ Std# Platform (lbs#)	Base Frame Width (inches)	Base Frame Length (inches)	Minimum Platform Width (inches)	Minimum Platform Length (inches)	Maximum Platform Width (inches)	Maximum Platform Length (inches)	Raising or Lowering Time Loaded (seconds)	Motor Size (hp)	Number of Cylinders	Shipping Weight Approx# (lbs#)	Standard Hydraulic Power Unit
24S25EXW	24	2500	6.5	30.5	2500	2500	48	36	48	36	72	60	16	1.5	2	715	INTERNAL
24S40EXW	24	4000	6.5	30.5	4000	4000	48	36	48	36	72	60	16	1.5	2	715	INTERNAL
24S60EXW	24	6000	6.5	30.5	4500	4500	48	36	48	36	72	60	16	1.5	2	715	INTERNAL
24S80EXW	24	8000	7	31	4500	4500	48	36	48	36	72	60	22	1.5	2	825	INTERNAL
36S25EXW	36	2500	6.5	42.5	2500	2500	48	48	48	48	72	72	25	1.5	2	855	INTERNAL
36S40EXW	36	4000	6.5	42.5	3500	3500	48	48	48	48	72	72	25	1.5	2	855	INTERNAL
36S60EXW	36	6000	6.5	42.5	3500	3500	48	48	48	48	72	72	25	1.5	2	855	INTERNAL
36S80EXW	36	8000	7	43	3500	3500	48	48	48	48	72	72	34	1.5	2	965	INTERNAL
48S25EXW	48	2500	7	55	2500	2500	48	64	48	64	72	96	33	1.5	2	1095	INTERNAL
48S40EXW	48	4000	7	55	3500	3500	48	64	48	64	72	96	33	1.5	2	1095	INTERNAL
48S60EXW	48	6000	7	55	3500	3500	48	64	48	64	72	96	33	1.5	2	1095	INTERNAL
48S80EXW	48	8000	7.5	55.5	3500	3500	48	64	48	64	72	96	44	1.5	2	1210	INTERNAL
58S120EXW	58	12000	12.5	70.5	12000	10000	61	90	61	90	90	120	60	5	2	5400	INTERNAL
58S150EXW	58	15000	12.5	70.5	14000	12000	61	90	61	90	90	120	60	5	2	5500	INTERNAL
60S25EXW	60	2500	8	68	2500	2500	58	87	58	87	84	120	44	1.5	2	2300	INTERNAL
60S40EXW	60	4000	8	68	3500	3500	58	87	58	87	84	120	44	1.5	2	2350	INTERNAL
60S60EXW	60	6000	8	68	4500	3500	58	87	58	87	84	120	44	1.5	2	2400	INTERNAL
60S80EXW	60	8000	12	72	6000	6000	61	90	61	90	90	120	36	5	2	5200	INTERNAL
60S100EXW	60	10000	12	72	10000	9000	61	90	61	90	90	120	36	5	2	5300	INTERNAL



GLOBAL SALES GROUP, LLC

Global Sales Group, LLC  
P.O. Box 1835  
Chico, CA 95927  
Offc: 530-893-2444  
Fax: 530-893-2244  
[www.globalsalesgroupllc.com](http://www.globalsalesgroupllc.com)

Authorized Dealer for Autoquip