



# EDGE BANDERS



**Authorized Dealer:**

Global Sales Group, LLC  
P.O. Box 1835 \* Chico, CA 95927  
Toll Free: 877-474-5521  
Office: 530-893-2444  
[www.globalsalesgroupllc.com](http://www.globalsalesgroupllc.com)



[www.cantekamerica.com](http://www.cantekamerica.com)

# MX550AU

## PORTABLE EDGE BANDER PACKAGE

The MX550 is a portable edgebander with digital temperature and variable speed control. It is built to suit the needs of both professionals and hobbyists alike. It combines the features of a stationary edgebanding station, hot melt glue application, speed feeding, and temperature control, with the convenience of a handheld tool. The MX550 is perfect for on-site work or integration into your woodworking shop.



### TECHNICAL SPECIFICATIONS

|                      |   |
|----------------------|---|
| Tape Thickness       | 0.4 - 3 mm  |
| Width of Tape        | 10 - 65 mm  |
| Feeding Speed        | 0.1 ~ 6 M/mm                                      |
| Output Power         | 1065W, 1 Phase                                    |
| Glue Pot Temperature | 120 °C - 200 °C ± 1 °C<br>(250 °F - 390 °C ± 2°F) |
| Glue Pot Capacity    | 400 ml  |
| Unit Weight          | 8.7 kgs   |

### ERGONOMIC, INTUITIVE CONTROLS

#### Rubber Grips and Metal Support Plate

Two rubber grips allow for precise control, while a metal support plate designed to rest on the workpiece allow for strain-free use.

#### Easy On/Off Switch

The feeder on/off switch is located on top of the primary handle, allowing for immediate control of the tool's operation

#### Adjustable Glue Pot Handle

The glue pot handle has two positions in case of work piece interference.

#### Tape Insert Guide

A measured guide in increments of 1mm determines the width of the edgeband or edging tape and secures it in place for a regulated feed.

#### Consistent Glue Application

A knob allows for on-the-fly regulation of glue amount for a mess-free, consistent result.

#### Digital Temperature Monitor

A digital temperature monitor provides accurate control over glue application. Temperature ranges are 120°C - 200°C ±1°C (250°F - 390°F ±2°F)



Comes with the trolley too!



MX550  
Edgebander



TK65  
Dual End Cutter



(1) Unit of glue



VH03  
Vacuum Clamp Set



PD80  
Power Trimmer