



TA SERIES

TABLE SAWS



Authorized Dealer:
Global Sales Group, LLC
P.O. Box 1835
Chico, CA 95927
Toll Free: 877-474-5521
Office: 530-893-2444
www.globalsalesgroupllc.com

 PMB #104 1124 Fir Avenue
Blaine, WA 98230

 T: 1.888.982.2683
F: 604.540.1780

 Youtube // @CantekMachinery
Twitter // @CantekMachinery

 www.cantekamerica.com
sales@cantekamerica.com



TA SERIES

TABLE SAWS



BLADE ADJUSTMENT HANDWHEELS

Blade raising/lowering & tilting handwheels with locking handles. Easy to read angle gauge.



T-SQUARE STYLE RIP FENCE

Fast and accurate fence adjustment with T-square design. Magnifying glass display makes reading measurements even easier. Dual Inch and Metric tape.



BLADE TILT

Right tilting blade to 45°. Heavy-duty cast iron saw carriage and work table. The work table is ground and polished.



MITRE GAUGE

Cast iron mitre gauge runs in either of two slots in the work table, one to the right and one to the left of the blade.



SAFETY BLADE GUARD

Safety blade guard is included with clear plastic guard, riving knife, and anti-kickback pawls for safe operation.



MAGNETIC STARTER SWITCH

Magnetic starter is to UL/CSA standards.

STANDARD EQUIPMENT



Dado Arbor Extension & Dado Insert

FEATURES

- Heavy-duty cast iron table is precision ground for accuracy
- Rugged machine frame construction provides maximum stability and reduced vibration
- Precision rip fence assembly locks on front rail for a precise parallel reference to the saw blade
- Dual Inch/Metric scale guide rail on rip fence with magnifying glass for easy visibility
- Heavy-duty cast iron saw assembly
- Saw guard with safety anti-kickback unit
- Mitre gauge with two mitre slots in the table
- Two handwheels for blade tilting, raising/lowering w/ locking knobs
- CSA magnetic switch with overload protection
- Less saw blade

SPECIFICATIONS

	TA10	TA12	TA14	TA1214	TA16
Saw Blade Diameter	10"	12"	14"	14"	16"
Max. depth of cut at 90°	3"	4"	5"	5"	5 1/2"
Max. depth of cut at 45°	2"	2 3/4"	3 1/2"	3 1/2"	3 7/8"
Arbor diameter	5/8"	1"	1"	1"	1"
Arbor speed	4200 RPM	4000 RPM	3750 RPM	3750 RPM	3750 RPM
Table size	36"x27"	48"x30"	48"x38"	48"x38"	48"x38"
Table height	34 1/4"	34 1/4"	34 1/4"	34 1/4"	34 1/4"
Max. rip to right of blade	50"	50"	50"	50"	50"
Motor	3HP	5HP	7 1/2 HP	10 HP	10HP
Net weight	407lb	572lb	847 lbs	847 lbs	869 lbs