



Authorized Dealer:
 Global Sales Group, LLC
 P.O. Box 1835 * Chico, CA 95927
 Toll Free: 877-474-5521
 Office: 530-893-2444
 www.globalsalesgroupllc.com



SP-3400



SP-30



SP-35G

SP-3400 1/2" & 3/4" 2HP Shaper

SP-30 3/4" & 1" 3HP Shaper

SP-35G 1" & 1-1/4" 5HP Shaper

Options:

- SP-3012 1/2" SPINDLE for SP-30
- SP-114S 1-1/4" SPINDLE for SP-30
- SP-305C 2-PCS ROUTER BIT COLLECTOR SET

Features:

- Precision ground cast iron table and T-slot miter gauge slot.
- Perfect alignment, rigid spindle supported by a power transfer system for accuracy.
- Individual micro adjustments fence on both sides of spindle by hand wheels.
- Large hand wheel for fast movement and lock protection.
- Magnetic switch for overload protection.
- Spindle travel operated by a rack and scroll gear.
- Two spindle speeds for versatile cutting.
- Forward and reverse switch for cutting directions.
- Heavy gauge metal cabinet base.
- Alloy steel spindle for durability usage.
- Sealed long-life ball bearings.
- Standard equipment: Full power motor, dust chute, table inset, spring hold-downs, miter gauge.

SPECIFICATIONS	SP-3400	SP-30	SP-35G
Table Dimensions	20" x 24"	28" x 30"	30" x 40"
Spindle Speed (RPM)	8000 / 10000	8000 / 10000	4000 / 6000 / 8000 / 10000
Standard Spindle Dia.	3/4" & 1/2"	1" & 3/4"	1-1/4" & 1"
Spindle Travel	3"	3 1/4"	3"
Spindle Under Nut (1")	4"	4"	5"
Spindle Tilt	---	---	---
Table Insert	5" & 3 1/2"	7" & 3 1/2"	7" & 3 1/2"
Motor	1 1/2 HP, 1 PH	3 HP, 1 PH	5 HP, 3 PH
N.W.	260 LBS	330 LBS	740 LBS
G.W.	300 LBS	460 LBS	820 LBS

(Training and installation, tooling & rigging are optional)
 (Customer is responsible for local regulations and connecting utilities)

SP-35G

