



Authorized Dealer:
Global Sales Group, LLC
P.O. Box 1835 * Chico, CA 95927
Toll Free: 877-474-5521
Office: 530-893-2444
www.globalsalesgroupllc.com



ST-301FD 1 PH 4-Speed 3-Roller Feeder

ST-303FD 3 PH 4-Speed 3-Roller Feeder

Features:

- With the powerful feeding strength, one can freely & simply assemble, dismantle & adjust it. It may be installed onto the circular saw, shaper, sander, router, planer serving as one's invisible third hand at work.
- There are three (3) feed rollers on this feeder. Each roller has a suspender to hold simultaneously the workpiece at different degrees of thickness. It is also used to help the feed pressure.
- In case you need a large space between the rollers, you can take off the middle roller so the remaining rollers may be used for curve driving.
- For spindle molder, the feeder may be adjusted to the leveling direction for side feed to meet the requirement of various processing condition.
- There are two (2) sets of matching & interchangeable gears of variable sizes to create for stages of feeding speed.
- Forward & reverse feeding switch.
- Universal support stand with cast iron base, main bracket, thick refaced column and aluminum hand wheels for vertical and horizontal positioning.

Options:

- ST-30FRL EXTRA ROLLER FOR ST-30
- ST-30BT EXTRA BASE FOR ST-30

SPECIFICATIONS	ST-301 FD	ST-303 FD	ST-321 FD
Feeding Speed (Ft/Min)	13, 26, 36, 72	13, 26, 36, 72	16, 24, 28, 35
Roller Size (D x W)	4-3/4" 2-3/8"	4-3/4" x 2-3/8"	3-1/8" x 1-3/16"
Motor	1 HP, 1 PH, 230 V	1 HP, 3 PH, 230V	¼ HP, 1 PH, 110 V
Roller Suspension	1"	1"	½"
N.W.	134 LBS	134 LBS	44 LBS
G.W.	147 LBS	147 LBS	50 LBS

(Training and installation, tooling & rigging are optional)
(Customer is responsible for local regulations and connecting utilities)