

Castaly Multiple Boring Head A-3CW Series

Specifications	Dimensions						
	A	B	C	D	E	F	G
A-3CW14	0.39" (10 mm)	0.39" (10 mm)	1" (28 mm)	2" (55 mm)	5" (121 mm)	2" (58 mm)	0.12" (3 mm)
A-3CW20					6" (150 mm)	3" (71 mm)	
A-3CW22					6" (162 mm)	3" (76 mm)	
A-3CW26					8" (191 mm)	4" (92 mm)	
A-3CW36					3" (72 mm)	10" (251 mm)	

Specifications	Dimensions				
	H	L1	L	X	Y
A-3CW14	1" (18 mm)	4" (107 mm)	5" (132 mm)	2" (40 mm)	3" (73.8 mm)
A-3CW20	1" (17 mm)	4" (112 mm)	5" (137 mm)	2" (46 mm)	4" (88.8 mm)
A-3CW22		4" (114 mm)	5" (139 mm)		
A-3CW26	1" (15 mm)	5" (118.5 mm)	6" (143.5 mm)	3" (70.7 mm)	3" (70.7 mm)
A-3CW36		6" (141 mm)	7" (166 mm)		

Specifications	Spacing			Weight	
	Min	Max	Max Capacity	Thread	
A-3CW14	1" (14 mm)	3" (88 mm)	Ø0.39" (Ø10 mm)	m8x1.25 m10x1.5	6 LBS (2.7 kg)
A-3CW20	1" (20 mm)	4" (112 mm)	Ø1" (Ø15 mm)		9 LBS (4 kg)
A-3CW22	1" (22 mm)	5" (128 mm)	Ø1" (Ø20 mm)		11 LBS (4.8 kg)
A-3CW26	1" (26 mm)	6" (152 mm)	Ø1" (Ø30 mm)		16 LBS (7.2 kg)
A-3CW36	1" (36 mm)	8" (200 mm)	Ø2" (Ø50 mm)		28 LBS (12.8 kg)



P.O. Box 1835
 Chico, CA 95927
 Toll Free: 877-474-5521
 E-Mail: info@globalsalesgroupllc.com
 Web Site: www.globalsalesgroupllc.com