

Castaly Multiple Boring Head A-4CW Series

Specifications	Dimensions					
	A	B	C	D	E	G
A-4CW34	0.39" (10 mm)	0.39" (10 mm)	1" (28 mm)	2" (55 mm)	5" (121 mm)	0.12" (3 mm)
A-4CW42					6" (145 mm)	
A-4CW48					7" (170 mm)	
A-4CW58					8" (192 mm)	
A-4CW78				3.15" (80 mm)	10" (260 mm)	

Specifications	Dimensions				
	H	L1	L	X	Y
A-4CW34	1" (15 mm)	5" (115 mm)	6" (140 mm)	3" (70.7 mm)	3" (70.7 mm)
A-4CW42		5" (117 mm)	5" (132 mm)		
A-4CW48		4" (109 mm)	5" (134 mm)		
A-4CW58		5" (118.5 mm)	6" (143.5 mm)		
A-4CW78		6" (145 mm)	7" (170 mm)		

Specifications	Spacing			Weight	
	Min	Max	Max Capacity	Thread	
A-4CW34	Ø1" (Ø34 mm)	Ø4" (Ø94 mm)	Ø0.39" (Ø10 mm)	m8x1.25 m10x1.5	11 LBS (4.8 kg)
A-4CW42	Ø2" (Ø42 mm)	Ø4" (Ø114 mm)	Ø1" (Ø15 mm)		14 LBS (6.3 kg)
A-4CW48	Ø2" (Ø48 mm)	Ø5" (Ø132 mm)	Ø1" (Ø20 mm)		17 LBS (7.7 kg)
A-4CW58	Ø2" (Ø58 mm)	Ø6" (Ø158 mm)	Ø1" (Ø30 mm)		23 LBS (10.4 kg)
A-4CW78	Ø3" (Ø78 mm)	Ø8" (Ø206 mm)	Ø2" (Ø50 mm)		43 LBS (19.5 kg)



P.O. Box 1835
 Chico, CA 95927
 Toll Free: 877-474-5521
 E-Mail: info@globalsalesgroupllc.com
 Web Site: www.globalsalesgroupllc.com