



Authorized Dealer:
Global Sales Group, LLC
P.O. Box 1835 * Chico, CA 95927
Toll Free: 877-474-5521
Office: 530-893-2444
www.globalsalesgroupllc.com



SPECIFICATIONS	CL-35CS
Range of Stock Length	4" ~ 35"
Range of Stock Diameter	3/8" ~ 2-3/8"
Production Rate	20 ~ 30 PCS/MIN
Saw Blade Speed	3400 RPM
Blade Saw Motor	1/2 HP
Feeder Drum Drive Motor	1/4 HP
Net Weight	800 LBS
Gross Weight	1230 LBS

CL-35CS Double End Rod Cut Off Saw Machine

Features:

- Designed and built well-suited for double end cut off operations for the stock with round section, in cylindrical, tapered or irregular shaped. The machine also can perform center cut off for relative short stock. High cut off efficiency speed, up to 30 cycles per minute.
- Range of stock diameter from 3/8" to 2-3/8".
- Feed loader can be adjusted to suit for various diameters of stock. Saw head slides on precision machined dovetail ways, saw blades are perfectly square to stock, that enables cut off surface straight and smooth.
- The feeder drum is 3 speeds selection.
- Stock rest can be adjusted to suit for various cylindrical stock diameters or tapered diameters.
- The entire cut off operation is fully automatic, stock is holding down by V-belt, without chattering during cutting.
- In application for center cut off, there is a locking rest fitted to feeder drum to ensure positive drop down of cut off stock.
- Automatic cut off sequence: Stock enters into feeder drum from feeder loader, feeder drum is rotating continuously that feeds the stock against saw blade for cutting, after cut, the rotating feeder drum automatic carry out the stock and drop it.

(Training and installation, tooling & rigging are optional)
(Customer is responsible for local regulations and connecting utilities)