

## Castaly Rear Load Beam Saw TS-P330R/ 380R

Specifications		TS-P330R	TS-P380R
Capacity	Max. Cutting Length	126" (3200 mm)	150" (3800 mm)
	Max. Cutting Height	0 ~ 4", Optional: 5" (0-100 (Optional: 120 mm))	
Main Sawblade	Diameter	Ø16" (Ø18") (Ø405 mm (Ø455 mm))	
	Arbor Diameter	Ø2" (Ø60 mm)	
	Speed	3910 RPM	
Scoring Sawblade	Diameter	Ø7" (Ø180 mm)	
	Arbor Diameter	Ø2" (Ø45 mm)	
	Speed	5100 RPM	
Saw Carriage	Forward Speed	5 ~ 100 M/ min	
	Return Speed	120 M/ min	
Motor	Main Sawblade Motor	20 HP (Optional: 25 HP)	
	Scoring Sawblade Motor	3 HP	
	Saw Carriage Drive Motor	1 KW	
	High Pressure Blower Motor	5 HP	
	Automatic Feed Motor	1 KW (AC Servo Motor)	
Lifting Table	Hydraulic Motor	5 HP	
	Horizontal Motion Motor	1 HP	
	Max. Loading Capacity	7 Tons	
Other	Pusher Feed Speed	5 ~ 80 M/ min	
	Working Air Pressure	7 kg/cm <sup>2</sup>	
	Table Height from Floor	40" (1020 mm)	



Global Sales Group, LLC  
P.O. Box 1835  
Chico, CA 95927  
Toll Free: 877-474-5521  
E-Mail: [info@globalsalesgroupllc.com](mailto:info@globalsalesgroupllc.com)  
Web Site: [www.globalsalesgroupllc.com](http://www.globalsalesgroupllc.com)