


Authorized Dealer: Global Sales Group, LLC P.O. Box 1835 * Chico, CA 95927 Toll Free: 877-474-5521 Office: 530-893-2444 www.globalsalesgroupllc.com





BS-1212HR12" Horizontal Band Rip SawBS-1616HR16" Horizontal Band Rip Saw

Features:

- Machine was built with rugged construction throughout for maximum stability, high precision cutting and minimum trouble.
- It is equipped with a digital controller for convenient and accurate thickness setting.
- The feed conveyor has a tilting design allowing for maximum 30-degree bevel cuts.
- When the feed conveyor is tilted for bevel cutting, a side support is applied for safe and stable cutting operations.
- Variable feed speed is controlled by a frequency inverter for best cutting requested.
- The infeed and outfeed pressure rollers are easily raised or lowered by a gear rack.
- The infeed and outfeed pressure rollers are spring-loaded and easily adjusted for the horizontal or vertical direction to suit various workpiece thicknesses.
- Blade tension is adjusted by means of a hand wheel.
- A tension scale allows the operator to correctly adjust the tension for different blade thickness.
- The cast iron saw blade wheel is dynamically balanced for smooth running.
- Blade guard is easily lifted up, supported by two nitrogen gas cylinders for convenient blade change.
- The roller type return conveyor equipped at left side of the machine provides easy repetitive cutting.

| SPECIFICATIONS | BS-1212HR | BS-1616HR |
|---|--------------------|-------------------|
| Max.Working Width | 12" | 16-1/2" |
| Max. Working Height (under Pressure Roller) | 12" | 16' |
| Distance between Blade to Conveyor | 1/8"to 10-5/8" | 1/4" ~ 12" |
| Saw Wheel Diameter | 28" x 2 | 32" x 2 |
| Saw Blade Length (Width) | 196" (1" ~ 2") | 230-3/4" (2"~4") |
| Saw Blade Speed | 6000 FPM | 6150 FPM |
| Feed Conveyor Size (W x L) | 10-5/8" x 165-1/2" | 16" x 165-1/2" |
| Feed Conveyor Tilt Degree | 0~30 | ~ |
| Return Conveyor (L x W x H) | ~ | 100" x 24" x 32" |
| Feed Speed (Variable) | 0 ~ 60 FPM | 0 ~ 60 FPM |
| Main Motor | 20 HP | 30 HP |
| Saw Blade Lift Motor | 1/2 HP | 1/2 HP |
| Feed Conveyor Motor | 1 HP | 2 HP |
| Return Conveyor Motor | ~ | 1 HP |
| Dust Hood | 4" x 2 | 4" x 2 |
| Machine Size | 88" x 85" x 74" | 128" x 130" x 78" |
| N.W. | 2900 LBS | 4000 LBS |