




**Authorized Dealer:**  
 Global Sales Group, LLC  
 P.O. Box 1835 Chico, CA 95927  
 Toll Free: 877-474-5521  
 Office: 530-893-2444  
 www.globalsalesgroupllc.com

# HB600

## 24" VERTICAL BAND RESAW


### FEATURES

- Heavy fabricated steel machine frame
- Specially designed Bakelite guide blocks provide rigid side blade support for straight cutting
- Large cast iron work table is precision ground and can tilt to a maximum of 45°
- Convenient blade tension adjustment by means of a handwheel and gauge
- Cast iron upper and lower saw wheels are precision machined and dynamically balanced
- Rack & pinion blade guide adjustment
- Wheel is crowned for proper blade tracking and added stability of the blade
- Foot brake for braking wheels and blade
- Including Electrics to UL/CSA



#### Blade Guide

Bakelite fitted on the blade guide assembly provides extra rigid side support



#### Tilting Table

Table can be manually tilted from 0 to 45 degrees



### OPTIONAL AF19 POWER FEEDER



The AF19 Bandaw Power Feeder is spring loaded and includes a roller fence for smooth and even feeding through a bandsaw for mid to heavy-duty workloads.

- 1/2 HP motor
- 10 Speeds ranging from 4 - 60 fpm
- Serrated Roller 175 X 40mm
- Spring-loaded cover to adjust to workpiece size
- Scaled roller fence included

### SPECIFICATIONS

Saw wheel diameter	24"
<b>Motor</b>	<b>7 1/2 HP</b>
Table size	31 1/2" x 23-7/8"
Table tilting	0 - 45°
Throat capacity	22-7/8"
Height capacity	13 3/4"
Width of wheel	2.677" (68mm)
Blade speed	4458 FPM
Blade length	173" to 175-3/8"
Blade width	3"
Dust hood diameter	4" x 1
<b>Electrics</b>	<b>230/3/60 = 22 Full Load Amps</b>
Net weight	750 lbs.
Machine size	41 3/4" x 31 1/2" x 81 1/2"