



HB800

HEAVY DUTY BAND RESAW

Authorized Dealer:

Global Sales Group, LLC
P.O. Box 1835 * Chico, CA 95927
Toll Free: 877-474-5521
Office: 530-893-2444
www.globalsalesgroupllc.com

FEATURES

- Heavy fabricated steel machine frame
- Specially designed Bakelite guide blocks provide rigid side blade support for straight cutting
- Large cast iron work table is precision ground and can tilt to a maximum of 45°
- Convenient blade tension adjustment by means of a handwheel and gauge
- Cast iron upper and lower saw wheels are precision machined and dynamically balanced
- Rack & pinion blade guide adjustment
- Wheel is crowned for proper blade tracking and added stability of the blade
- Foot brake for braking wheels and blade
- Blade lubrication system and reservoir for lubricant keeps blades cool
- Including Electrics to UL/CSA - all starters
- Auto Start-Delta control for main motor with Emergency Stop Switch
- Telemecanique brand magnetic switch

HF-150A FEEDER

- 1HP motor with variable feed speed from 16 – 66 FPM
- Pneumatic tensioned feed roller
- Feed pressure is adjustable
- Feed roller opening and closing is controlled by a foot switch for operator convenience
- Knurled steel roller

RESAW SPECIFICATIONS

Saw wheel diameter	32"
Motor	20HP
Table size	45 1/4" x 31 1/2"
Table tilting	0 – 45°
Throat capacity	30-5/8"
Height capacity	15-3/8"
Width of wheel	3.543" (90mm)
Blade speed	5024 FPM
Blade length	216" to 217-1/8"
Blade width	4"
Dust hood diameter	4" x 2
Electrics	230/3/60 = 54 Full Load Amps 460/3/60 = 27 Full Load Amps

FEEDER SPECIFICATIONS

Length of roller	6"
Diameter of roller	8"
Feed speed	16 – 66 FPM
Motor	1HP
Air pressure	5 kg/cm2
Fence adjustment	4.72"
Feed opening	6"
Net weight	242 lbs.

