

# AF19N RESAW FEEDER



#### **Authorized Dealer:**

Global Sales Group, LLC P.O. Box 1835 \* Chico, CA 95927 Toll Free: 877-474-5521

Office: 530-893-2444 www.globalsalesgroupllc.com

# Consistent and reliable automatic feeder for your resaw or bandsaw.

The Cantek AF19N Resaw Feeder is designed to allow consistent and automated feeding of material through vertical bandsaw or resaws. The AF19N is pneumatically actuated by a switch in the fence so no foot pedal is required making for a simple and convenient operation. With 10 feed speeds to choose from you can dial in the optimum feed speed for your material. Intended to be fit on bandsaws which are 24" and larger but could be fitted on smaller bandsaw tables, but may require an extension off the side of your bandsaw table where the feeder is mounted.



## Key Advantages.

- Consistent feeding for bandsaws and resaws
- Pneumatic activation of feeding unit, no foot pedal required
- 10 feed speeds for optimum control
- Line bar roller fence is easily adjusted by rack and pinion handle
- Comes with (2) adjustable steel serrated rollers
- Can be mounted to almost any bandsaw/resaw (recommended for 24" and up)
- Heavy duty construction
- Adjustable feed wheels to accommodate for the height of your material
- Roller fence aids in feeding of material

## Specifications.

Feed Speeds (10) 4/8.5/8.5/14/17/25/28/30/50/60 FPM

Roller size  $\Phi$ 6-7/8"x 1-9/16" x 2 pcs / Cast Steel

Motor 1/2 HP (0.375 KW), 3 phase; Forward

Maximum roller stroke 8"

Fence dimensions 16" x 7 7/8"

Max. Roller-Blade Clearance 8 1/4"

Net Weight 79 Kg

Gross Weight 97 Kd

Packing Size 48" x 18-7/8" x 18-1/2"

Cantek America Inc. | www.cantekamerica.com | PMB #104 1124 Fir Avenue Blaine, WA 98230 | sales@cantekamerica.com | 1.888.982.2683