



PMB #104, 1124 Fir Ave
Blaine, WA 98230
Tel: 1(888)982-2683
Email: sales@cantekamerica.com

HB-950A / HB-600 VERTICAL BAND SAW(RESAW)

http://www.sawyer.com.tw

www.cantekamerica.com

Designed for Curve and Rip Cutting - In a Single Band Saw!



HB-950A



HB-600A

2 in 1 Machine for Rip and Curve Sawing

Now you have a choice of combining scroll sawing and rip sawing in the one machine. Very heavy-duty design with an affordable price.



MITER GAUGE

Manufactured from cast aluminum, this miter gauge is suitable for straight and angle cutting. It provides 60° angle adjustment at the right and the left side with easy-to read graduated scale.



BLADE GUIDE

Convenient side guide adjustment is made through micrometric adjustment knob for narrow blades. Blade guide mechanism is equipped with bearing, providing rigid back-up support of blade.



The table can be tilted 45° front downward by direct hand tilting.




Laminated with wider 2"(50 mm.) rubber.

SAW WHEEL

The saw wheel suits blade widths from 1/4" to 2"(50MM) making this machine ideal for curve cutting and rip cutting.

The saw wheels are laminated with rubber for accurate blade tracking. Positive grip and maximum blade durability.



BLADE ADJUSTMENT MECHANISM

1. Blade guide fixing knob
2. Blade guide raising hand wheel
3. Blade track adjustment knob
4. Blade tension hand wheel
5. Blade tension indicator

SPECIFICATIONS

MODEL	HB-600A	HB-950A
SAW WHEEL DIAMETER	600 mm (23-1/2")	940 mm (37")
TABLE SIZE	800 x 605 mm (31 - 1/2" x 23 - 3/4")	1150 x 800 mm (45 - 1/4" x 31 - 1/2")
TABLE TILTING	0° ~ 45°	0° ~ 45°
THROAT CAPACITY	580 mm (28 - 3/4")	927 mm (36" ~ 1/2")
HEIGHT CAPACITY	350 mm (13 - 3/4")	560 mm (22")
WIDTH OF WHEEL	50 mm(2")	50 mm(2")
BLADE SPEED	710 RPM (4458 F.P.M)	533 RPM (5500 F.P.M)
BLADE LENGTH	4410~4480 mm (173-5/8" ~ 176 - 1/2")	6580~6630mm (259"~261")
BLADE WIDTH	6.3 mm~50 mm(1/4" ~ 2")	6.3 mm ~50 mm(1/4" ~ 2")
DUST HOOD DIAMETER	ø4" x2	ø4" x2
MOTOR	5 HP	10 HP
NET WEIGHT	340 kg	720 kg
GROSS WEIGHT	450 kg	930 kg
MACHINE SIZE (L x W x H)	1060 x 800 x 2070 mm	1620 x 830 x 2880 mm
PACKING SIZE (L x W x H)	2160 x 630 x 1100 mm	2970 x 760 x 1550 mm

Design and specifications are subject to change without prior notice.