




PMB #104, 1124 Fir Ave.
Blaine, WA 98230
Toll Free: 1.888.982.2683
Email: sales@akhurst.com

www.cantekamerica.com

Saw Wheel Laminated with Rubber






- The side guide is micrometrically adjustable providing convenient adjustment for narrow blades.
- The saw wheel are laminated with rubber for accurate blade tracking and slippage prevention.
- The table is made of cast iron and the surface is precision ground. The table can tilt to a maximum of 45 degrees, front downward, for bevel cuts.
- Blade tension can be conveniently adjusted by means of a hand wheel. A tension scale allows the operator to correctly adjust the tension for different blade widths.
- The see-trough guard provides operator safety and protection.
- The foot brake permits the shutdown of machining operations.
- The heavy gauge steel frame ensures stable and vibration-free cutting.
- 4" diameter exhaust supplied as standard.



Convenient side guide adjustment is made by a micrometric adjustment knob for use with narrow blades.

HB-450, HB-500R, HB-600R, HB-700R

VERTICAL BAND SAW



RUBBER LAMINATED SAW WHEEL

The saw wheels on models HB-450R, HB-500R, 600R and 700R are Laminated with rubber for accurate blade tracking, a positive grip and maximum blade durability.

SPECIFICATIONS

MODEL	HB-450R	HB-500R	HB-600R	HB-700R
SAW WHEEL DIAMETER	450 mm (18")	500 mm (20")	600 mm (24")	700 mm (28")
TABLE SIZE	610 x 500 mm (23 - 1/2" x 19")	680 x 520 mm (26 - 3/4" x 20 - 1/2")	800 x 608 mm (31 - 1/2" x 20 - 1/2")	1000 x 700 mm (39 - 3/8" x 27 - 5/8")
TABLE TILTING	0° ~ 45°	0° ~ 45°	0° ~ 45°	0° ~ 45°
THROAT CAPACITY	430 mm (17")	475 mm (18" ~ 3/4")	580 mm (22 - 7/8")	678 mm (26 - 3/4")
HEIGHT CAPACITY	245 mm (9 - 3/8")	300 mm (11 - 7/8")	350 mm (13 - 3/4")	420 mm (16 - 1/2")
WIDTH OF WHEEL	30 mm	35 mm	35 mm	40 mm
BLADE SPEED	995 RPM (4685 F.P.M)	850 RPM (4450 F.P.M)	710 RPM (4458 F.P.M)	680 RPM (4980 F.P.M)
BLADE LENGTH	3855~3885 mm (151" - 3/4" x 153")	3969~3999 mm (156 - 1/4" x 157 1/2")	4410~4480 mm (173 - 5/8" x 176 - 3/8")	5130~5180 mm (202" x 204")
BLADE WIDTH	6.3 mm~32 mm (1/4" ~ 1 - 1/4")	6.3 mm~32 mm (1/4" ~ 1 - 1/4")	6.3 mm~32 mm (1/4" ~ 1 - 1/4")	6.3 mm~32 mm (1/4" ~ 1 - 1/4")
DUST HOOD DIAMETER	ø4" x 1	ø4" x 1	ø4" x 1	ø4" x 1
MOTOR	2 HP, 220 V, 1 Ph	2 HP	3 HP	5 HP
NET WEIGHT	210 kg	280 kg	315 kg	450 kg
GROSS WEIGHT	280 kg	350 kg	450 kg	600 kg
MACHINE SIZE (L x W x H)	860 x 560 x 1890 mm	970 x 700 x 1880 mm	1060 x 800 x 2070 mm	1330 x 900 x 2290 mm
PACKING SIZE (L x W x H)	1970 x 560 x 890 mm	1970 x 580 x 1010 mm	2160 x 630 x 1100 mm	2380 x 650 x 1210 mm

Design and specifications are subject to change without prior notice.