

<b>Specifications</b>	<b>BS-700</b>	<b>BS-800</b>
<b>Saw Wheel Diameter</b>	28" (700 mm)	31½" (800 mm)
<b>Table Size</b>	39-3/8" x 28-5/8" (1000 x 700 mm)	45¼" x 31½" (1150 x 800 mm)
<b>Table Tilting</b>	0° ~ 45°	0° ~ 30°
<b>Throat Capacity</b>	27¾" (678 mm)	31-5/8" (778 mm)
<b>Height Capacity</b>	16½" (420 mm)	15-3/8" (390 mm)
<b>Width of Wheel</b>	3" (75 mm)	3½" (90 mm)
<b>Blade Speed</b>	600 RPM	
<b>Blade Length</b>	200¾" ~ 202¾" (5100 ~ 5150 mm)	216" ~ 217-1/8" (5485 ~ 5515 mm)
<b>Blade Width</b>	3" (75 mm)	4" (100 mm)
<b>Dust Hood Diameter</b>	Ø4" x 2	
<b>Motor</b>	7.5 HP	15 HP
<b>N. W.</b>	1103 LBS (500 kg)	1466 LBS (665 kg)
<b>G. W.</b>	1433 LBS (650 kg)	1940 LBS (880 kg)
<b>Machine Size (L x W x H)</b>	52" x 35" x 90" (1330 x 900 x 2290 mm)	59" x 37" x 95" (1500 x 930 x 2420 mm)
<b>Packing Size (L x W x H)</b>	94" x 28" x 48" (2380 x 720 x 1210 mm)	100" x 33" x 56" (2530 x 850 x 1410 mm)