

Specifications	BS-1616HR
Max. Cutting Capacity	16½" x 16-1/8" (420 x 410 mm)
Distance Between Blade to Conveyor	¼" x 10-5/8" (5 ~ 270 mm)
Minimum Cut Thickness	¼" (5 mm)
Saw Wheel Diameter	32" (800 mm) x 2
Saw Blade Length	231" ~ 231.1" (5860 ~ 5870 mm)
Saw Blade Width	2" (50 mm)
Saw Blade Speed	6150 FPM
Conveyor Belt Sizes (W x L)	16" x 165½" (400 x 4200 mm)
Feed Speed (Variable)	40" (1016 mm)
Return Conveyor Size	100-3/8" x 24¾" x 32½" (2550 x 630 x 825 mm)
Conveyor Height From Floor	40" (1016 mm)
Return Conveyor Motor / Inverter Motor	1HP 3Ø / 2HP 3Ø
Saw Wheel Motor	30 HP
Blade Lift motor	½ HP
Dust Hood Outlet Diameter	4" (100 mm) x 2
Machine Dimension (L x W x H)	128" x 130" x 79" (3250 x 3300 x 2000 mm)
Packing Dimensions (L x W x H)	108" x 89" x 87" (2750 x 2250 x 2200 mm)
N. W.	4321 LBS (1960 kg)
G. W.	4763 LBS (2160 kg)